


DATA SHEET

POLYMAX 1M012B

CONSTRUCTION			DATA			
TOP COVER	Material	PVC		HARDNESS	Top cover	80 SHORE A
	Cover structure	SMOOTH			Bottom cover	SHORE A
	Colour	SORT		ANTISTATIC PROPERTIES		
INTERMED. LAYER	Material		TEMPERATURE RANGE	Min.	-15 ° C	
	Colour			Max.	80 ° C	
BOTTOM COVER	Material	FABRIC	PULLEY-DIAMETER			
	Cover			<u>1: Normal flex</u>		
	Colour			min. Ø =	10 [mm]	
UPPER FABRIC	Warp		<u>2: Back flex</u>			
	Weft		min. Ø =	20 [mm]		
INTERMED.FABRIC	Warp		WORKING TENSION (NOM.)			12 [N/mm]
	Weft		PULL FOR ELONGATION 1% (MIN.)			9 +/- 0,5 [N/mm]
BOTTOM FABRIC	Warp	POLYESTER	WEIGHT			1,25 [Kg/m ²]
	Weft	POLYESTER/MONOFIL	COEF.FRICTION (STEEL)			0,15 +/- 0,02
TOP COVER THICKNESS		0,40 [mm]	APPROVAL			
BOTTOM COVER THICKNESS		[mm]				
TOTAL THICKNESS		1,00 [mm]				

ADDITIONAL INFORMATION	
SPECIAL FEATURES	
APPLICATIONS	AGRICULTURAL INDUSTRY DISTRIBUTION CENTRALS (POST, NEWSPAPERS, AIRPORTS, TERMINALS) ELECTRONICS INDUSTRY TEXTILE INDUSTRY
JOINING METHODS	SINGLE FINGER SPLICING MECHANICAL SPLICING
	